# BE-1708A1-V

## 8-Port 17.3” LCD/VGA KVM Switch

.





## Accessories



or






## LCD KVM features:

| No | Part | Function Description |
|---|---|---|
| 1 | Handle | Pull this handle to pull out the KVM module; push this handle to push back the KVM module. |
| 2 | LCD display | Support Auto power ON/OFF while opening & closing the monitor if there is certain degree angle ,supporting DDC/DDC2B |
| 3 | LCD control button | LCD switch button and control LCD screen position and image setting. |
| 4 | Keyboard | Support keyboard with backlight for typing comfort. |
| 5 | Touchpad | |
| 6 | Rack bracket | The rack is at the two sides of the equipment, used to fix the bottom of the equipment on the rack. |
| 7 | Buckle | Push in this buckle before the console can be pushed and pulled freely on the rack. |
| 8 | Lock and indicating lamps | Indicating lamp of Num Lock, Caps Lock and Scroll Lock respectively. |
| 9 | Quick Button | 8x Quick buttons support switching to each port. |

## Specifications

| Model No | BE-1708A1-V (17.3”LCD) |
|---|---|
| Display Size | 17.3’’ |
| Panel Type | SXGA TFT |
| Resolution | 1920x1080@60Hz |
| PC Port | 8 |
| Best control distance | 5m |
| Interface Attribute | VGA |
| Keyboard | Standard 104 Keyboard |
| Mouse | Touchpad with two button |
| Operation | By OSD,HotKey,Panel |
| Angle of visibility | 80/80/60/80(Typ.)(CR≧10) |
| Brightness | 350 cd/$m^2$ (Typ.) |
| Contrast | 600:1(Typ.) |
| Power Consumption | 15W |
| Power Supply | AC100～240V 50～60Hz |
| Operation Tempture | 0°C ~50°C |
| Storage Tempture | -20°C ~60°C |
| Humidity | 0~80%RH |
| Weight | 11kg |
| Dimension(DxWxH) | 450mmx450mmx42mm |

## Ordering Information

| | |
|---|---|
| BE-1708A1-V | 8-Port 17.3”LCD /VGA KVM Switch |